



Applications:

Perfect for security, entry ways, stairways, storage and perimeter areas, as well as residential exteriors.

Features

- Sealed die-casting profile for outdoor applications
- Consumes 17W to replace 120W Incandescent, 25W to replace 50W HID
- Lumen output from 1600-2200lm
- Polycarbonate optical lens with UV stabilizers for choosing
- Built-in UL class 2 driver, and 120V/277V photocell
- UL/cUL listed and DLC qualified



Housing

Better waterproofing, and suitable for both indoor and outdoor application

Lens

Polycarbonate optical lens with heat resisting. Clear and frosted lens optional for different applications.

Photocell

Optional allows for security and energy saving

Mounting

Supports direct wall mounting and J-box mounting, with 1/2 inch entry at the bottom

PERFORMANCE DATA


				5000K	
Wattage	Voltage	Lens	CRI	Lumes	LPW
17W	120-277VAC	Clean Lens	80	1700lm	100lm/w
25W	120-277VAC	Clean Lens	70	2600lm	104lm/w

ELECTRICAL DATA


Number Of Drivers	Driver Current (mA)	Nominal Power (W)	INPUT VOLTAGE (V)	CURRENT (Amps)
1	620	17	120	0.14
		17	208	0.08
		17	240	0.07
		17	277	0.06
1	890	25	120	0.21
		25	208	0.12
		25	240	0.10
		25	277	0.09

DIMENSION

unit: inch/mm




89.5mm (3.52in.)



Weight:
17W: 2.039lb
25W: 2.039lb

PHOTOMETRICS

Clear Lens



ORDERING GUIDE

Fixture Type	Wattage	Voltage	CCT	Finish	Photoce (Option)	Lens
WM Wall Mount	17 17W 25 25W	27V 120-277V	50K 5000K	D Dark Bronze	P2 277V Photocell	Blank Clear Lens